

SunTONE®



Full Shade	PRODUCT NAME	C.I.Name	APPLICATIONS						PROPERTIES			
	SunTONE® Code Number		LDPE	HDPE	PP	Rubber/ EVA	PVC	Engineering Plastic	Light Fastness Full Tone	Light Fastness Tint Tone	Heat Stability in °C	Migration
	YELLOW 3361	PY 12	•	•	•	•	•		4-5	3-4	200	3-4
	YELLOW 339K	PY 13	•	•	•	•	•		6-7	6	200	3-4
	YELLOW 342	PY 14	•	•	•	•	•		5	3	200	3-4
	YELLOW 351	PY 17	•	•	•	•	•		6-7	6	200	3
	YELLOW 3186	PY 62	•	•	•	•	•		7	6	240	4-5
	YELLOW 3249	PY 83	•	•	•	•	•		7	6	200	4
	YELLOW 3414	PY 138	•	•	•	•	•	◦	8	7	240	5
	YELLOW 3417	PY 139	•	•	•	•	•	◦	7	7	240	5
	YELLOW 3453	PY 151	•	•	•	•	•	•	8	7	290	5
	YELLOW 3504	PY 168	•	•	•	•	•		7	7	250	4-5
	YELLOW 3549	PY 183	•	•	•	•	•	•	8	7	280	4-5
	YELLOW 3573	PY 191	•	•	•	•	•	•	7	7	300	4-5
	ORANGE 793K	PO 13	•	•	•	•	•		5	3-4	200	3-4
	ORANGE 7112	PO 16	•	•	•	•	•		6	4	220	4-5
	ORANGE 7238	PO 34	•	•	•	•	•		6-7	5-6	200	4
	ORANGE 7448	PO 64	•	•	•	•	•	•	8	7	300	5
	RED 5240	PR 48.1	•	•	•	•	•		5-6	4	240	4
	RED 5241	PR 48.2	•	•	•	•	•		6	4	240	4-5

LIGHT FASTNESS : 1 TO 8 (1 Indicates very very poor, 8 Indicates Excellent)

MIGRATION : 1 TO 5 (1 Indicates Heavy Migration, 5 Indicates No Migration)

•: Recommended; ◦: Can Use

SunTONE®

Full Shade	PRODUCT NAME	C.I.Name	APPLICATIONS						PROPERTIES			
	SunTONE® Code Number		LDPE	HDPE	PP	Rubber/ EVA	PVC	Engineering Plastic	Light Fastness Full Tone	Light Fastness Tint Tone	Heat Stability in °C	Migration
	RED 5242	PR 48.2	•	•	•	•	•		6	4	240	4-5
	RED 5245	PR 48.3	•	•	•	•	•		6-7	5	240	4-5
	RED 5266K	PR 53.1	•	•	•	•	•		5	2-3	260	4-5
	RED 5266LB	PR 53.1	•	•	•	•	•		5	2-3	260	4-5
	RED 5287K	PR 57.1	•	•	•	•	•		5-6	3-4	240	4
	RED 5562	PR 112	•	•	•	•	◦		5-6	3-4	200	4
	RED 5850	PR 170	•	•	•	•	•	◦	7-8	7	260	2-3
	RED 5851	PR 170	•	•	•	•	•	◦	7-8	7	260	2-3
	RED 5611K	PR 122	•	•	•	•	•	•	8	8	300	4-5
	RED 51270	PR 254	•	•	•	•	•	•	7-8	7	300	4-5
	BLUE 9151K	PB 15.1	•	•	•	•	•		7-8	7	280	3-4
	BLUE 9153K	PB 15.3	•	•	•	•	•		7	6	280	5
	BLUE 9261	PB 29	•	•	•	•	•	◦	7-8	7	260	4-5
	GREEN 107K	PG 7	•	•	•	•	•		7-8	7	300	4-5
	VIOLET 1123	PV 23	•	•	•	•	•		8	7	260	5
	YELLOW 2222	PY 34	•	•	•	•	•	◦	7	6	240	4-5
	YELLOW 2232	PY 34	•	•	•	•	•	◦	7	6	240	4-5
	ORANGE 4245	PR 104	•	•	•	•	•	◦	7	6	240	4-5

LIGHT FASTNESS : 1 TO 8 (1 Indicates very very poor, 8 Indicates Excellent)
 MIGRATION : 1 TO 5 (1 Indicates Heavy Migration, 5 Indicates No Migration)
 •: Recommended; ◦: Can Use